



UNIVERSITI PUTRA MALAYSIA

**NITRATE LEACHING IN SOILS TREATED WITH ACTIVATED
SLUDGE, CATTLE MANURE AND CHEMICAL FERTILIZERS**

NOOSHIN MOSTOFI

FK 2009 91

**NITRATE LEACHING IN SOILS TREATED WITH ACTIVATED SLUDGE,
CATTLE MANURE AND CHEMICAL FERTILIZERS**

By

NOOSHIN MOSTOFI

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia,
in Fulfilment of the Requirements for the Degree of Master of Science**

January 2009



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment of the requirement for the degree of Master of Science

**NITRATE LEACHING IN SOILS TREATED WITH ACTIVATED SLUDGE,
CATTLE MANURE AND CHEMICAL FERTILIZERS**

By

NOOSHIN MOSTOFI

January 2009

Chairman: Thamer Ahmed Mohamed, PhD

Faculty: Engineering

Nitrogen fertilizers have been recognized as an important factor in crop's yield level, however more application of N fertilizers in the soil have some adverse effects on environment and especially on ground water contamination. Perception and recognition the factors influencing nitrate transport through soil profile is helpful for fertilizer management to minimize adverse impacts on environment and nitrate leaching below the root zone. In this study, 15 large cylindrical lysimeters with 1 m height and 0.56 m diameter were filled with clay and sandy loam soil and planted with maize to investigate nitrate leaching under different types of N-fertilizer; activated sludge (20 ton/ha), cattle manure (40 ton/ha) and chemical fertilizer (containing 70 kg N/ha). Also 3 lysimeters with 1.4 m height were used to investigate the effect of soil depth in nitrate leaching in sandy loam soil. Totally the study involved nine treatments. Nitrate concentrations in the soil and drainage water samples were analyzed by spectrophotometer method and nitrate mass were calculated in irrigation water, soil and drainage water. Crop production for different

treatments has been compared too. The nitrate-N concentrations were higher than 10 mg N/L (the maximum acceptable concentration) in 60% of the observations for OFcl. The Nitrate-N concentrations were higher than 10 mg N/L in 48 and 51% of the samplings for the CFcl and OFcl treatments, respectively. The Nitrate-N concentrations were almost always lesser than 10 mg/L in the lysimeters containing sandy loam soil. Results illustrate nitrate leaching from activated sludge and organic fertilizer in clay loam soil was significantly greater than the other treatments (110 kg/ha and 229 kg/ha respectively). Among all treatments of this study organic manure in clay loam soil had the greatest nitrate accumulation in soil (15.17 mg/kg) and chemical fertilizer in sandy loam soil had the least (8.56 mg/kg). Experimental results also showed that manure application could result in NO_3^- -N accumulation increase in the deeper soil profiles compared with mineral fertilization and activated sludge. The results demonstrate that nitrate, from the activated sludge and chemical fertilizers, transported through the soil profile is more than the organic manure after the 75 cm depth, and the accumulation of organic fertilizer is mostly 60 to 90 cm depth from the soil surface.

Keywords:

Activated sludge, chemical fertilizer, ground water contamination, nitrate leaching, organic manure, soil type

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Master Sains

**RESAPAN NITRAT KE DALAM TANAH YANG TELAH DIRWAT
DENGAN BAHAN KUMLOAHAN AKTIF, BAJA BERASAKAN KIMIA DAN**

NAJIS HAIWAN

Oleh

NOOSHIN MOSTOFI

Januari 2009

Pengerusi: Thamer Ahmed Mohamed, PhD

Fakulti: Kejuruteraan

Baja Nitrogen sememangnya telah dikenalpasti sebagai satu faktor yang penting dalam tahap pengeluaran hasil tanaman, walaupun bagaimanapun lebih kadar penggunaan baja Nitrogen ke atas tanah boleh mendatangkan impak negatif terutamanya untuk alam sekitar dan pencemaran air bawah tanah. Adalah penting untuk mengenalpasti dan mengetahui faktor-faktor yang mempengaruhi kadar resapan nitrat melalui lapisan tanah dalam perkara pengurusan baja untuk mengurangkan impak negatif terhadap alam sekitar dan juga pengaliran nitrat di bawah pada zon akar tanaman. Dalam kajian ini, 15 buah silinder lysimeter berukuran 1 m tinggi dan 0.56 m garispusat telah dipenuhi dengan tanah liat dan tanah gembur berpasir dan seterusnya ditanam dengan maize untuk dilakukan ujikaji kadar resapan nitrat untuk baja Nitrogen yang berbeza; sisa aktif (20 ton/ha), baja organik (40 ton/ha) dan baja kimia (mengandungi 70 kg N/ha). 3 buah lagi silinder lysimeter berukuran 1.4 m tinggi telah digunakan untuk mengkaji kesan kedalaman

tanah dalam kadar resapan nitrat untuk tanah gembur berpasir. Keseluruhannya 9 jenis rawatan yang berbeza telah dilakukan. Kepekatan nitrat di dalam tanah dan sampel air saliran telah diuji dengan kaedah spectrophotometer dan berat nitrat dikira dalam tanah, air pengairan dan saliran. Hasil tanaman untuk semua jenis rawatan yang berbeza juga telah dibuat perbandingan. Kepekatan N-nitrat adalah lebih tinggi berbanding 10 mg N/L (kepekatan maksimum yang boleh diterima) dalam 60% pemerhatian untuk OFcl. Kepekatan N-Nitrat adalah lebih tinggi daripada 10 mg N/L dalam 48 dan 51% sampel rawatan CFcl dan OFcl masing-masing. Kebiasaannya, kepekatan N-Nitrat adalah lebih rendah berbanding 10 mg/L dalam lysimeters yang mengandungi tanah gembur berpasir. Keputusan ujian menunjukkan resapan nitrat dari sisa aktif dan baja organik dalam tanah liat menunjukkan jumlah yang jauh lebih tinggi berbanding dengan rawatan-rawatan yang lain (masing-masing 110 kg/ha dan 229 kg/ha). Di dalam kajian ini baja organik bagi tanah liat menunjukkan kadar pengumpulan nitrat dalam tanah yang tertinggi (15.17 mg/kg) dan baja kimia di dalam tanah gembur berpasir menunjukkan jumlah yang paling rendah (8.56 mg/kg). Hasil eksperimen juga menunjukkan penggunaan baja boleh menyebabkan peningkatan $\text{NO}_3\text{-N}$ terkumpul terutamanya bagi lapisan tanah yang lebih dalam berbanding dengan baja mineral dan sisa aktif. Keputusan ujian menunjukkan bahawa nitrat dari sisa aktif dan baja kimia dibawa melalui profil tanah adalah lebih berbanding baja organik bagi kedalaman melebihi 75 cm, dan kebiasaannya pengumpulan baja organik adalah di antara kedalaman 60 hingga 90 cm dari permukaan tanah.

Kata Kunci

Sisa aktif, baja kimia, pencemaran air bawah, resapan nitrat, baja organik, jenis tanah

I dedicate this thesis to my beloved country, Iran

And

To my parents, Nosratollah Mostofi and Maliheh Maali...your essence is in

everything I accomplish...

ACKNOWLEDGEMENTS

My prayerful thanks to my Merciful God, source of all knowledge and wisdom, who gives me every thing I have. You have made my life more bountiful. May your name be exalted, honored, and glorified.

It is a pleasure to thank the people who made this thesis possible. I especially want to thank my supervisor Dr. Thamer Ahmed Mohammed for his continuous aid and helpful advices. Especially I want to thank him for giving me the chance of working in my country Iran.

I am grateful to my co-supervisor Ir. Megat Johari for his guidance and editing expertise. I was delighted by attending his classes and having him as my co-supervisor.

I would like to express my deep gratitude and grateful thanks to my Iranian supervisor Dr. Abdolmajid Liaghat, head of Irrigation and Reclamation Department of Tehran University, for his support and confidence. He always found time to guide me through my work although he was too busy.

I am grateful to Sara, Sanaz, Samaneh, Nazanin and Amin for being amazing friends and classmates. It would have been difficult to complete this project and graduate school without their support, laughter, and understanding. I wish all of my classmates the best with their future endeavors.

I have spent nice moments in my second country, Malaysia, country of people from different cultures and religions who live together in peace. I would like to thank people of Malaysia, whom I have learned a lot from them.

I would like to thank my dear brother, Bahram, for his generous supports. And at last my deepest gratitude goes to my parents for their unflagging love and continued supports throughout my life. They have always inspired me to persevere through the hard times. I greatly appreciate them, for their patience, calmness and encouragement. They have worked industriously to support our family and spare no effort to provide the best environment for me to grow up. I love them and I always feel proud of them.

I certify that an Examination Committee has met on 22 January 2009 to conduct the final examination of Nooshin Mostofi on her Master of Science thesis entitled “Nitrate leaching in soils treated with activated sludge, cattle manure and chemical fertilizer” in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree) Regulations 1981. The Committee recommends that the student be awarded the Master of Science.

Members of the Examination Committee were as follows:

Name of Chairperson, PhD

Professor
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Name of examiner 1, PhD

Professor
Faculty of Engineering
Universiti Putra Malaysia
(Internal Examiner)

Name of examiner 2, PhD

Professor
Faculty of Engineering
Universiti Putra Malaysia
(Internal Examiner)

Name of external examiner, PhD

Professor
(External Examiner)

BUJANG KIM HAUT, PhD

Professor and Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: 09 April 2009

This thesis was submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfilment of the requirement for the degree of Master of Science. The members of supervisory committee were as follows:

Thamer Ahmed Mohamed, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Megat Johari Megat Mohd. Noor

Associate Professor Ir.
Faculty of Engineering
Universiti Putra Malaysia
(Member)

HASANAH MOHD GHAZALI, PhD

Professor and Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: 09 April 2009

DECLARATION

I declare that the thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously and is not concurrently submitted for any other degree at UPM or at any other institutions.

.....

NOOSHIN MOSTOFI

Date: 12 September 2009

TABLE OF CONTENT

	Page
ABSTRACT	ii
ABSTRAK	iv
ACKNOWLEDGMENTS	vii
APPROVAL	ix
DECLARATION	xi
LIST OF TABLES	xiv
LIST OF FIGURES	xvi
LIST OF ABBREVIATIONS	xviii
 CHAPTER	
 1 INTRODUCTION	 1
1.1 General	1
1.2 Statement of the problem	2
1.3 Objectives	4
 2 LITERATURE REVIEW	 5
2.1 Effects of N Fertilizers	5
2.1.1 Cattle Manure Characteristics	5
2.1.2 Activated Sludge	7
2.1.3 Fertilizers	8
2.2 Nitrate Absorption Cycle in Soil	12
2.2.1 Mineralization	12
2.2.2 Nitrification	14
2.2.3 Immobilization	15
2.2.4 Denitrification	16
2.3 Nitrate Leaching and Its Effects	17
2.4 Ground Water Contamination by Nitrate in the World	19
2.5 Ground Water Contamination in Iran	23
2.6 Health Concerns	26
2.7 Effect of Soil on Nitrate Movement	28
2.8 Effect of Water Table	31
2.9 Summaries of Literature Review and Motivation of This Study	32
 3 MATERIALS AND METHODS	 35
3.1 General	35
3.2 Location	35
3.2.1 Iran	36
3.2.2 Site Description	38

3.3	Climates	39
3.4	Lysimeters	40
3.4.1	Construction Processes	40
3.4.2	Filling the Lysimeters with Soil	48
3.4.3	Planting and Crop Water Requirement	50
3.5	Nitrate Measurements for Drainage Water	54
3.6	Nitrate Measurements of Soils	56
3.7	Mass of Nitrate	58
3.8	Irrigation Water	58
3.9	Fertilizers	59
3.9.1	Chemical Fertilizer	59
3.9.2	Activated Sludge	60
3.9.3	Cattle Manure	61
3.10	Water Table Control	62
3.11	Statistical Analysis	62
4	RESULTS AND DISCUSSION	63
4.1	Monthly Climatic Data	63
4.2	Water Balance	65
4.3	Nitrate Concentration and Mass in Drainage Water	67
4.4	The Concentration of Nitrate in the Soil	92
4.5	The Mass of Nitrate in the Soil	100
4.6	The Effect of Fertilizers on Products	102
5	SUMMARY, CONCLUSION AND RECOMMENDATIONS FOR FUTURE RESEARCH	104
5.1	Conclusion	104
5.2	Recommendation for future research	108
	REFERENCES	110
	APPENDICES	120
	BIODATA OF STUDENT	137

LIST OF TABLES

Table	Page
2.1 Chemical properties of cattle manure	7
2.2 Chemical properties of activated sludge	8
2.3 Guidelines for drinking water quality from (WHO)	27
2.4 Guidelines for drinking water quality from (EPA)	28
2.5 Summary of some similar studies	34
3.1 Physical and chemical properties of soils	49
3.2 Water requirement for maize in Karaj	51
3.3 Properties of irrigation water	52
3.4 Chemical characteristics of fertilizers	59
4.1 Climatic data	63
4.2 Monthly water inputs, drainage, evapotranspiration and temperature during the experimental period	66
4.3 Nitrate concentration (mg/L) in drainage water samples during eleven weeks	69
4.4 Statistical analysis for nitrate-N concentrations in drainage water	70
4.5 The mean nitrate concentrations in ppm (mg/L) for the different treatments the during eleven weeks' period	72
4.6 Soil properties at the beginning and the end of the season	76
4.7 Nitrate concentration in similar studies	80
4.8 Cumulative nitrate mass (mg) in the drained water during the season	88
4.9 Statistical analysis for nitrate-N mass in drainage water	89

4.10	Cumulative nitrate mass (kg/ha) in drained water for three treatments during the season	91
4.11	Nitrate mass (mg of nitrate per kg of soil) in the soil extracts of different depths	93
4.12	Comparison to another similar study	99
4.13	Nitrate mass (g) in lysimeters of each treatment	101
4.14	Comparison between products of different treatments	103

LIST OF FIGURES

Figure	Page
2.1 Nitrogen transformations in nature	14
3.1 Location of Karaj city in the map of Iran	39
3.2 Lysimeters with 1.4 m height during installation of drain pipes	41
3.3 1m height lysimeters during installation of drain pipes	42
3.4 Drain pipe inside the barrel (left), joint of barrel and drain pipe inside the barrel (right)	43
3.5 Schematic views of lysimeters	45
3.6 Site of experiment after installation of stages	46
3.7 Stages before installation of lysimeters	47
3.8 One of the lysimeters after installation	47
3.9 Filling the lysimeters with soil	50
3.1 Lysimeters 2 weeks after planting	52
3.11 Lysimeters in September 2007	53
3.12 Lysimeters before harvesting	53
3.13 Eighteen samples of drainage water, preparing blanks and samples, samples after addition of sulfuric acid and the spectrophotometer	55
3.14 Soil sampling with auger	57
3.15 Soil samples after being pulverized	57
3.16 Soil extracts in shaker	58
3.17 Lysimeter containing chemical fertilizer solved in water	60
3.18 Lysimeter containing activated sludge	61
3.19 Lysimeter containing cattle manure	61
4.1 Precipitations during the experiment	64
4.2 Humidity and temperature	64

4.3	Maximum, minimum and mean temperature	65
4.4	Drainage water in mm for sandy loam lysimeters with 1 m height (top), sandy loam lysimeters with 1.4 m height (middle) and clay loam lysimeters (bottom)	67
4.5	Nitrate concentrations (mg/L) of Sandy loam treatments in lysimeters with 1 m height	79
4.6	Nitrate concentrations (mg/L) for Clay loam treatments in lysimeters with 1m height	82
4.7	Nitrate concentrations (mg/L) for the Sandy loam treatments in lysimeters with 1.4 m height	84
4.8	Cumulative nitrate mass (mg) for lysimeters containing clay and sandy loam soil with 1m height	85
4.9	Cumulative nitrate mass (mg) for lysimeters containing sandy loam soil with 1m and 1.4m height	87
4.10	Nitrate concentrations in the soil extracts for lysimeters containing sandy loam soil with 1 m height	94
4.11	Nitrate concentrations in soil extracts for lysimeters containing clay loam soil with 1m height	95
4.12	Nitrate concentrations in the soil extracts for lysimeters containing sandy loam soil with 1.4 m height	97

List of Abbreviations

Abbreviations	Meaning
AScl	Activated Sludge in Clay Loam soil
ASsl	Activated Sludge in Sandy Loam soil
EEC	European Economic Community
°C	Degrees Celsius
BD	Bulk Density
CFcl	Chemical Fertilizer in Clay Loam soil
CFsl	Chemical Fertilizer in Sandy Loam soil
Cmic	Microbial Biomass Carbon
D	Day
DMRT	Duncan Multiple Range Test
DNA	Deoxyribonucleic Acid
E	Energy
EC	Electrical Conductivity
EDTA	Ethylene Diamine Tetra Acetic Acid
EPA	Environmental Protection Agency
Ha	Hectare
Hr	Hour
L	Litre
L/capita.d	Litre per capita per day
Meq	Milli equivalents per liter
Mt/yr	Million ton per year
NPK	Nitrogen-Phosphorus-Potassium fertilizer
OFcl	Organic Fertilizer in Clay Loam soil
OFsl	Organic Fertilizer in Sandy Loam soil
P.V.C.	Poly Vinyl Chloride
RNA	Ribonucleic Acid
SAR	Sodium Adsorption Ratio
SAS	Statistical Analysis System
TKN	Total Kjeldahl Nitrogen
TP	Total Phosphorus
WHO	World Health Organization
Yr	Year

CHAPTER I

INTRODUCTION

1.1 General

The rising population of the world has directly placed significant pressure on various authorities and infrastructures, mainly in providing more food and water. In order to successfully feed the growing world's population, a continued increase in the production of food is therefore a necessity. Obviously, the areas under cultivation and renewable water resources are restricted all over the world. Hence, it is important to produce more crops per hectare so as to increase the amount of the food produced. One way of enhancing the production of crops is the usage of organic and inorganic fertilizers. However, some studies have shown that the continued use of fertilizers may result in a decline in the quality and productivity of soil. It is undeniably that fertilization is an important cause of groundwater contamination with nitrate in agricultural soils (Rimski-Korsakov *et al.*, 2004; Zebarth *et al.*, 1998 and Strebel *et al.*, 1989). Saving the world's water resources from contamination with chemicals and reuse of agricultural water is very important. This is specifically vital in the arid and semi-arid countries, where water scarcity is serious and ground water has an important role in providing drinking and irrigation water. In low precipitation regions, even reuse of drainage water extracted from the drainage system is required.

1.2 Statement of the Problem

A sustainable agricultural management will depend on a more efficient use of renewable resources, such as animal manure and sludge from waste water treatment processes. Nitrogen fertilizers are widely used in agriculture to synchronize the levels of soil available nitrogen with crop's nitrogen requirements during the season, to increase crops nitrogen uptake and to enhance the yield. After the growing season, a part of these organic or inorganic fertilizers remains in the soil and is converted to various forms of nitrogen such as nitrate. This nitrate can leave the root zone in heavy precipitation, and also by excessive irrigation even when land is cropped annually. Over application of fertilizers will generally cause nitrate accumulation in the soil and nitrate leaching via soil pores and cracks. Various long-term experimental studies have indicated that the accumulation of nitrate in soil is a result of interaction among the soil productivity; soil moisture status and the efficient use of nitrogen fertilizer (Yang *et al.*, 2006).

Plant takes up nitrogen mostly in inorganic form. This may partly explain why the N (nitrogen) uptake of plant from organic N sources is commonly found to be lower than that of inorganic N sources. The use of organic nitrogen sources presents challenges in N availability for crops. Organic farming still suggests organic fertilizers to take into account the environment and public health as the main concerns. The nitrogen which is not utilized during the cropping season may be mineralized outside the season and it becomes prone to leaching. The potential for N leaching is thus generally considered to be greater when manure is applied, as compared to inorganic fertilizer.

Statistical data show that the consumption of nitrogen fertilizer is growing rapidly in developing countries. High concentrations of NO_3^- in the surface water bodies can result in eutrophication, algal blooms, aquatic mortality, methemoglobinemia, gastric cancer, growth inhibition, thyroid hypertrophy, reproductive toxicity and ulceration of the mouth and stomach lining (Gupta et al., 1999b).

Nitrogen leaching in irrigated agriculture should receive considerable attention, because of possible pollution of groundwater. Nitrate pollution of groundwater is of particular concern because of the large number of people in city and rural areas relying on groundwater for drinking. Large amounts of N-fertilizer with poorly managed irrigated systems may lead to NO_3^- leaching and pollution of groundwater. In this study, the impact of nitrate leaching was investigated in order to minimize the pollution of the groundwater with best fertilization management practices.

Integration of knowledge, related to environmental conditions of a certain area with the soil, water and crop management practices, helps to prevent the simultaneity of the unfavourable processes leading to nitrate leaching. In this way, water resources may be protected from nitrate pollution of agricultural origin. Contamination of ground water depends on many factors, including the soil type, climate, geological and agricultural practices. The effective approach to minimize the movement of nitrate into groundwater is to develop a site-specific improved N fertilization and irrigation management practices to increase the N uptake efficiency, decrease N loss, and minimize leaching losses below the root zone.

Measuring and predicting nitrate concentration and mass loading from agricultural activities as non point source of pollution for groundwater seems to be useful for pollution control. In this study, quality of the drainage water and mass of nitrate leaching was monitored to provide information for different kinds of fertilization practices.

1.3 Objectives

The objectives of the study include:

1. To compare the movement of nitrate in two soil types (clay and sandy soil);
2. To compare the various types of fertilizer (cattle manure, chemical fertilizer and activated sludge) in the case of nitrate movement:
 - I) to assess the accumulation and movement of nitrate in the soil profile;
 - II) to determine the concentration of nitrate in drainage water;
 - III) to survey on the mass of nitrate-N leaching;
3. To assess the effect of soil depth in nitrate leaching.

CHAPTER II

LITERATURE REVIEW

2.1 The Effects of N Fertilizer

High yielding crops require a substantial supply of N, and most crops prefer to take up N as nitrate. A good supply of nitrate in the soil is an asset, but too much of it is a liability (Sethi, 2005). Under applying N can result in decreased yields and profits, while over application can potentially increase the accumulation of nitrate-N (NO_3^- -N) in soils and the potential losses to ground and surface waters (Tarkalson *et al.*, 2006).

2.1.1 The Characteristics of Cattle Manure

Animal manure is a valuable resource, both as a nutrient and as a soil conditioner. In organic farming, where the use of mineral nitrogen fertilizer is prohibited, a high utilization of nutrients in manure is especially important. Part of the animal manure is handled as solid manure where urine and feces are mixed with bedding material often consisting of cereal straw (Thomsen, 2001).

The determination of crop available N from manures is based on the contents of NH_4^+ , NO_3^- and organic N in the manure. Solid manures such as cattle manure

collected from feedlot surfaces have a large proportion of the N in the organic fraction (Tarkalson *et al.*, 2006)

However, it is difficult to predict the availability of manure N to plants since both N turnover processes and losses of manure N influence its availability. The net mineralization of manure N is variable, and at the same time, there may be net immobilization of N during a period following the application of manure, mainly after the application of anaerobically stored manures (Sørensen, 2001). Manured soils have higher contents of organic C and N, but lower pH and bulk densities as compared to soils receiving various mineralized fertilizers, especially the ones which are lacking P, indicating that a long-term application of manures could efficiently prevent the leaching of applied N from and increase N content in the ploughed layer (Meng *et al.*, 2005).

In general, when organic manures are added to soil, an ideal condition for denitrification will develop. Labile forms of organic C are used as an energy source by a large population of heterotrophic microbes. When the biological O₂ demanded by microbes exceeds the supply, the anaerobic microenvironment necessary for denitrification is created. In addition, the application of organic manures stimulates the production of N₂O through nitrification, as this process is also increased when aeration becomes restricted (Meng *et al.*, 2005). Some chemical characteristics of cattle manure (Antoun, 1982), are shown in (Table 2.1).